

# Cab-n-Connect™ A300

More efficient. More performance.



## Cabin Wireless Access Point - 802.11be / Wi-Fi 7

- 802.11 a/b/g/n/ac/ax/be backwards compatibility
- Dedicated smart sensor for top-level security and performance
- Support for WPA3 security certifications
- DO-160G qualified hardware
- Two Quadrax circular connectors for retrofit applications

Kontron's latest Cab-n-Connect A300 combines powerful 802.11be Wi-Fi 7 technology, advanced security and ML/AI management capabilities into a single enterprise-class solution that allows customers to deploy high speed, highly secure Wi-Fi in the toughest aircraft environments. Optimized for multi-platform video streaming, it provides the highest level of efficiency and performance for dense, multi-client applications running within the aircraft cabin.

With aggregated data rates up to 11.5 Gbps in the 6 GHz band, concurrent 1.2 Gbps in the 5 GHz band and concurrent 573Mbps in the 2.4 GHz band, this next generation CWAP provides intelligent edge capabilities with the highest level of client services without compromising security monitoring. It has been designed with passive cooling (fanless) technology to prevent the unit from overheating and comes with worldwide operations support.

With more users, more devices, more things, more applications and more threats straining aircraft infrastructure, the Cab-n-Connect A300 was engineered to meet a multitude of ongoing challenges. The Cab-n-Connect A300 is the only avionics-certified CWAP that offers a dedicated, Tri-band sensor that continuously scans and detects security threats in real-time eliminating the risk of vulnerability or attacks, while also

optimizing RF performance automatically. It delivers top-level security services, with support for the Wi-Fi Alliance's WPA3 security certifications, TPM for secure key storage.

In addition, Ace Flight™ Connect Firmware provides ease of use and a rich feature set. It is built from best-in-class open-source router / firewall software and is further enhanced by Kontron's integration of leading-edge security features.

The CWAP Cab-n-Connect A300 is engineered based on Kontron's innovative architecture and modular design approach. Benefits of this approach include:

- ▶ Leveraging state-of-the-art technology, while many enterprise WAPs are growing in dimensions and energy consumption, Kontron effectively minimizes the size, weight, and power of the CWAP hardware.
- ▶ The software solution is meticulously optimized for the avionics sector, ensuring enhanced management over the solution's entire lifecycle.
- ▶ This strategic design accelerates the product's time to market and simplifies the upgrade trajectory for forthcoming Wi-Fi technologies.

## Technical Information

RADIO OPERATION	TRI-RADIO TECHNOLOGY	2.4 GHz/5 GHz/ 6 GHz Multi-User MIMO (MU-MIMO) 802.11be: (6GHz) 4K QAM 802.11ax (6E): OFDMA (4096 QAM) 802.11ax: OFDMA (1024-QAM) 802.11ac: OFDM(BPSK, QPSK, 16-QAM, 64QAM, 256-QAM) 802.11ac Packet Aggregation: A-MPDU, A-MSDU 80 2.11ac Very High- Throughput (VHT): VHT20/40/80 802.11ac Advanced Features: LDPC, STBC, Maximum Likelihood (ML) 802.11n: OFDM (BPSK, QPSK, 16-QAM, 64-QAM) 802.11n High-throughput (HT) support: HT 20/40 802.11n Packet aggregation: A-MPDU, A-MSDU 802.11 802.11a: 6, 9, 12, 18, 24, 36, 48, 54 Mbps 802.11n: (2.4 GHz); 6.5 to 300 Mbps (MCS0 to MCS15, HT20 to HT40) 802.11n: (5 GHz); 6.5 to 300 Mbps (MCS0 to MCS15, HT20 to HT40) 802.11ac: (5 GHz) 6.5 to 3467 Mbps (MCS0 to MCS9, NSS=1to 4, VHT20 to VHT160) 802.11ax: (2.4 GHz): 3.6 to 574 Mbps (MCS0 to MCS11, NSS = 1to 2, HE20 to HE40) 802.11ax: (5 GHz): 72.1 to 1201 Mbps (MCS0 to MCS11, NSS = 1to 2, HE20 to HE80) 802.11ax: (6 GHz): 72.1 to 4804 Mbps (MCS0 to MCS11, NSS = 1to 4, HE20 to HE160) 802.11be: (6GHz): up to 11530 Mbps when using 320 MHz channels 6GHz mode Dedicated Sensor Radio for monitoring across all frequencies of 2.4 GHz/5 GHz/ 6 GHz band sensing is via a virtual radio BLE 5 Radio Bluetooth® Low Energy (BLE) and IEEE® 802.15.4 compliant
	DATA RATES	2.4GHz Radio – 256 Clients 5GHz Radio – 256 Clients 6GHz Radio – 512 Clients FCC CFR 47 Part 15, Class B, ICES-003 Class B, FCC Subpart C 15.247, FCC Subpart E 15.407, RSS247, EN 301 893, EN 300 328, EN 301 489 1 & 17, EN 50385, EN 55032 (CISPR 32), EN 60601-1-2
	RADIO FOR WIPS & BLUETOOTH	
	CLIENTS PER RADIO	
	RADIO APPROVALS	

ANTENNAS	7x integrated Omni-Directional Antennas
SOFTWARE	<p>Ace Flight™ Connect provides a rich feature-set of flexibility and scalability within a dense cabin aircraft environment offering (Not limited to):</p> <ul style="list-style-type: none"> <li>- Ease of configuration</li> <li>- Management via SSH, Telnet, SNMP, HTTP/HTTPS</li> <li>- Ease of Troubleshooting with the inbuilt tools such as Wireless Survey, Remote Syslog, Spectral Scan</li> <li>- Up-to-date security Standards such as WPA2, WPA3, Wireless ACL</li> <li>- Versatile Networking in AP, Router, Bridge modes with VLAN support</li> <li>- WIPS Support</li> <li>- Radius Server Support</li> <li>- Hotspot 2.0 Support</li> </ul> <p>Band Steering and Client Load Balancing</p> <ul style="list-style-type: none"> <li>- roaming within the network</li> <li>- field loadable software/updates</li> <li>- Automatic Failure Recovery with dual image configuration</li> </ul> <p>Dynamic Frequency Selection (DFS)</p>
FIRMWARE	<p>Low-Level Embedded Features</p> <ul style="list-style-type: none"> <li>- EEPROM Storage: Stores product details, accessible via CLI and displayed in the WEB GUI</li> <li>- Power On Self-Test: Runs hardware tests during boot, configurable and readable from SNMP and CLI</li> <li>- Dual-Bank Support: Supports dual boot bank upgrades with recovery mechanisms</li> <li>- Thermal Management: Protects against overheating by throttling CPU and radios</li> <li>- Firmware Upgrade: Supports upgrades over FTP/TFTP and DHCP</li> </ul> <p>Logging and Management</p> <ul style="list-style-type: none"> <li>- System Logging: Persistent logging with remote syslog support</li> <li>- Configuration Provisioning over DHCP: Uses DHCP server options to configure CWAP device</li> <li>- LED Indication: Covers mission mode radio status reporting and device identification</li> </ul> <p>Network Configuration</p> <ul style="list-style-type: none"> <li>- IP Strap: Configures IP address using hardware strapping</li> <li>- Zero Conf IP: Configures IP address using the MAC address of the interface</li> </ul> <p>Security Features</p> <ul style="list-style-type: none"> <li>- WIPS: Wireless Intrusion Prevention System with SNMP alarms</li> <li>- Secure Boot: Uses TPM for secure booting</li> <li>- Signed Firmware: Supports firmware upgrades using signed firmware</li> <li>- nDPI Firewall: Firewall based on Layer 7, block and control specific internet protocols</li> </ul> <p>Wireless Features</p> <ul style="list-style-type: none"> <li>- Hot Spot 2.0: Supports EAP-TLS secure connections</li> <li>- Wireless Security: Supports WPA2, WPA3, and other security protocols</li> <li>- Wi-Fi 7 Support: Supports Wi-Fi 7 with high throughput and multi-user load management</li> <li>- Bluetooth Support: Bluetooth Beacon (marketing use-case implementation)</li> </ul> <p>Advanced Wireless Capabilities</p> <ul style="list-style-type: none"> <li>- Roaming: Maintains continuous connection while moving between APs</li> <li>- VLAN to SSID: Allows specifying specific VLAN ID to SSID</li> <li>- Airtime Fairness: Distributes airtime between different VAPs on a single band</li> <li>- RF Operation and Control: Allows disabling Radio RF using discrete (RFKILL)</li> </ul> <p>Client Interfaces</p> <ul style="list-style-type: none"> <li>- SNMP: Supports configuration and statistics via SNMP interface</li> <li>- CLI: Command line interface for configuration and information</li> <li>- GUI: Web interface for configuration</li> <li>- REST API: Web services providing API for configuration &amp; monitoring</li> <li>- Role-Based User Management: Configurable user roles and rights for GUI and REST API services</li> </ul>
SECURITY	<p>IP filtering, NAT, 802.1x, 802.11i, WPA3, WPA2, WPA Triple Methodology</p> <p>Rogue Detection: 24x7 Tri-band WIPS sensing, on-board IDS and secure guest access Hotspot 2.0 with captive portal, TPM 2.0, Secure boot and Signed FW, RADIUS Server and VLANs</p>
RF MONITORING	Dedicated Tri-Band Sensor Radio that Intelligent monitors and detects security issues
I/O	<p>Two Quadrx Circular Connectors</p> <p>J1: Includes Input Power, Discrete I/O: Radio Disable/Enable; PWR On/Off; Status, 4x IP Strapping,</p> <p>J2: 2x 100/1000/2500 Mbps auto-negotiation Ethernet</p> <p>Supports Daisy-Chain and Fail-over feature for CWAP downstream fault recovery</p> <p>(2x 100/1000/2500 Mbps pass through)</p>
POWER	115 VAC/360-800 Hz Aircraft Grade power with 200 msec Hold-up; 30 W Nominal
ENVIRONMENT & EMI	Qualified to DO-160G
SIZE/DIMENSIONS (H X W X D)	2.88" (73.10 mm) x 9.5" (241 mm) x 6.8" (173mm) - Mounting per ARINC 836-1-7
WEIGHT	<4.45 lbs (2.0 kg)
OPERATING TEMPERATURE	-15 °C to +70 °C

# Ordering Information

ARTICLE	PART NO.	DESCRIPTION
CWAP, A300, LAB	73001015-001	LRU, CWAP, A300, LAB
CWAP, A300	73001015-101	LRU, CWAP, A300
CABLE KIT, A300, LAB	73001015-500	LAB CABLE KIT, A300

## Your Contact

### Kontron Canada Inc.

4555 Rue Ambroise-Lafortune  
Boisbriand (Québec), J7H 0A4, Canada  
Tel.: (800) 387-4222  
avionics@kontron.com

[www.kontron.com](http://www.kontron.com)

## Your Contact

### Kontron America Inc.

9477 Waples Street  
San Diego, CA 92121, USA  
Tel.: +1 888 294 4558  
avionics@kontron.com

[www.kontron.com](http://www.kontron.com)

## Global Headquarters

### Kontron Europe GmbH

Gutenbergstraße 2  
85737 Ismaning, Germany  
Tel.: +49 821 4086-0  
info@kontron.com

[www.kontron.com](http://www.kontron.com)

